

FCR1 R00 - EIA-530 / V.24 Cable - Product Code FS6073

For compatibility with the different FarSite adapter models check the [FarSite Network Connection Cables - Compatibility Matrix](#)

A label should be attached to the cable marked: **FCR1 R00**

The cable assembly shall be constructed with one end terminated in a high density 44-Way HD-Type plug (3 rows of pins) and the other end terminated in a 25-Way D-Sub plug. The Cable should contain shields of both foil and braid, the connector plugs must also be shielded.

The overall length of the cable assembly (HD44 to DB25) shall be 2.0 metres +/- 0.03m.

Twisted pairs must be maintained where indicated in the connection table for signal integrity.

The connections required are defined in the table below:

Interface Signal	HD44 Plug	DB25 Plug	Twisted Pairs	PORT
ATXDa / ATXD	16	2	PAIR	P O R T A
ATXDb	17	14		
ATXCa / ATXC	2	15	PAIR	
ATXCb	3	12		
ARXDa / ARXD	33	3	PAIR	
ARXDb	34	16		
ARXCa / ARXC	20	17	PAIR	
ARXCb	21	9		
ATTa / ATT	6	24	PAIR	
ATTb	7	11		
ARTSa / ARTS	31	4	PAIR	
ARTSb	32	19		
ACTSa / ACTS	18	5	PAIR	
ACTSb	19	13		
ADTRa / ADTR	22	20	PAIR	
ADTRb	23	23		
ADCDa / ADCD	35	8	PAIR	
ADCDb	36	10		
ADSRa / ADSR	4	6	PAIR	
ADSRb	5	22		
GNDa	37	7		
SHIELD	1+SHIELD	1+SHIELD		